

ZONE OVERPASS TOOL - FILE TRANSFER DOCUMENT

1. INTRODUCTION

This is the File Transfer Document for the ZoneOverPass executable program that calculates the entry and exit time when a given instrument swath passes over a zone or set of zones.

1.1 Change History

Issue	Change Description
1.3	First Issue
1.3.1	Update <i>mission_configuration_files</i> folder to v1.2
1.4	Update <i>mission_configuration_files</i> folder to v1.3 ZoneOverPass generates HTML output files Corrected path to ORBIT SDF for Aeolus
1.4.1	Update <i>mission_configuration_files</i> folder to v1.4
2.0	Distinguish between Ground Site (zone with num_points=1) and Zone in output files For Ground Site, calculate distance to ground track Swath filename in configuration file User-defined Swath identifier in configuration file Update <i>mission_configuration_files</i> folder to v1.5
2.0.1	Update <i>mission_configuration_files</i> folder to v1.6
2.1	Add support for TLE files Add support for non pre-defined missions (using satellite configuration file)

1.2 Distribution List

Project/Unit	Name	Project/Unit	Name	Project/Unit	Name

1.3 Reference Documents

[RD 01] Earth Observation Mission Software File Format Specification
 Ref. PE-ID-ESA-GS-584-1.1 - Issue 1.1- 21/03/17

[RD 02] OGC® KML Standard
 Ref. OGC 12-007r2 - Version: 2.3.0 - Date: 2015-08-04

2. ARCHIVE CONTENT

Separate archive files are available, to support execution in Linux, Mac OS X and Windows platforms.

2.1 Linux 64-bit

The following archive file has been delivered (compressed with the zip utility):
ZoneOverPass_LINUX64_v2_1_date_27_JUL_2018.zip

The archive has the following MD5 checksum:
cd9adc18f7744975169b9b222c87e42d

The archive contains the following files:

```
EXAMPLE_ZONEDBFILE.EOF
input_config_file_S2A_MSI.txt
input_config_file_S2A_ORBIT.txt
```

```
input_config_file_S3A_OLCI.txt
mission_configuration_files/...
overpass_table.css
Readme.txt
ZoneOverPass
```

2.2 Mac OS X 64-bit

The following archive file has been delivered (compressed with the zip utility):
ZoneOverPass_MACIN64_v2_1_date_27_JUL_2018.zip

The archive has the following MD5 checksum:
a7d73a47d08c44000496757cde079c64

The archive contains the following files:

```
EXAMPLE_ZONEDBFILE.EOF
input_config_file_S2A_MSI.txt
input_config_file_S2A_ORBIT.txt
input_config_file_S3A_OLCI
mission_configuration_files/...
overpass_table.css
Readme.txt
ZoneOverPass
```

2.3 Windows 32-bit

The following archive file has been delivered (compressed with the zip utility):
ZoneOverPass_WINDOWS32_v2_1_date_27_JUL_2018.zip

The archive has the following MD5 checksum:
5538ef907c299909eb890e00305a6e76

The archive contains the following files:

```
EXAMPLE_ZONEDBFILE.EOF
input_config_file_S2A_MSI.txt
input_config_file_S2A_ORBIT.txt
input_config_file_S3A_OLCI
overpass_table.css
pthreadVC2.dll
mission_configuration_files\...
Readme.txt
ZoneOverPass.exe
```

3. ARCHIVE CONTENT DESCRIPTION

The files contained in the archives are described in table below:

File	Description
EXAMPLE_ZONEDBFILE.EOF	Example Zone Database File
input_config_file_S2A_MSI.txt	Example configuration file of SENTINEL2A with MSI swath, with example zone database file
input_config_file_S2A_ORBIT.txt	Example configuration file of SENTINEL2A with ORBIT ground-track, with example zone database file
input_config_file_S3A_OLCI.txt	Example configuration file of SENTINEL3A with OLCI swath, with example zone database file
mission_configuration_files/...	Default input orbit files and swath files

Readme.txt		Readme file with example commands and input/output file description
overpass_table.css		CSS stylesheet file for HTML output
For LINUX 64-bit	ZoneOverPass	Executable file for Linux
For MAC OS X 64-bit	ZoneOverPass	Executable file for Mac OS X
For WINDOWS 32-bit	ZoneOverPass.exe	Executable file for Windows
	pthreadVC2.dll	Auxiliary pthread library for Windows

4. INSTALLATION

The archive can be expanded with Winzip / 7-zip (in MS Windows) or with the command unzip (in Linux/Mac OS).

5. USAGE

5.1 Executable program *ZoneOverPass*

For a requested UTC time interval, the executable program *ZoneOverPass* calculates the entry and exit times when a given instrument swath passes over a zone or set of zones. The program expects as input a configuration file setting the various input parameters, among them the mission name, orbit file, zone database file and instrument swath name.

The default orbit and swath characteristics are defined in the mission configuration files folder. It is possible to provide as orbit file other types of EOCFI-compatible OSV-based orbit files see ([RD 01]), e.g. Predicted Orbit File (ORBPRES file type) or Restituted Orbit Files (ORBRES file type).

The program generates a set of output files with the overpass tables per zone (in .CSV, .KML format and .HTML format).

5.1.1 Command line input parameters description

The command line parameters of the executable routine are the following (provided in the order in which they have to be supplied):

INPUT PARAMETERS	Definition	Value
Input Configuration File	Filename (it may include the path to the file)	Given by the user
UTC Start Time	UTC start time of the time interval CCSDS-A ASCII format with seconds (YYYY-MM-DDTHH:mm:ss)	Given by the user
UTC Stop Time	UTC stop time of the time interval CCSDS-A ASCII format with seconds (YYYY-MM-DDTHH:mm:ss)	Given by the user

5.1.2 Input configuration file format description

The contents of the input configuration file are detailed below:

INPUT PARAMETERS	Definition	Value
Satellite	Satellite identifier	AEOLUS CRYOSAT2 EARTHCARE METOPSG SENTINEL1A SENTINEL1B

		SENTINEL2A SENTINEL3A SENTINEL3B SENTINEL5P SMOS
Orbit Filename	Orbit Filename Default: Orbit Scenario Filename in mission_configuration_files folder	Given by the user
Instrument Swath	Instrument Swath Filename Default: Swath Definition Files in mission_configuration_files folder	Given by the user
Zone Database Filename	File with list of zones, in EO CFI / Esov NG Zone Database format	Given by the user
Instrument Swath	Instrument swath name (any string, based on available Swath Definition Files, e.g ORBIT, OLCI, MSI, SRAL, etc)	Given by the user
Swath Colour	Swath Color (aabbggrr, aa=alpha, bb=blue, gg=green rr=red, with ranges 00 to ff)	Given by the user

5.1.3 Output file format description

The executable program *ZoneOverPass* produces two output files per zone in Zone Database file:

- Comma Separated Value (.CSV)
- Google Earth KML file (.KML)
- Web browser HTML file (.HTML)

The output file names are automatically generated using the satellite identifier, the zone name, the swath name and the start and stop UTC times.

5.1.3.1 CSV Files

The CSV output file contains one row per each entry/exit visibility time segment, format of the CSV output file:

- Row 1-7: Header containing execution input information
- From Row 8:
 - Column 1: UTC Time Start in calendar format (CCSDS format “yyyy-mm-ddThh:mm:ss”)
 - Column 2: Absolute Orbit Start
 - Column 3: Start Seconds since Ascending Node Crossing (ANX)
 - Column 4: UTC Time Stop in calendar format (CCSDS format “yyyy-mm-ddThh:mm:ss”)
 - Column 5: Absolute Orbit Stop
 - Column 6: Stop Seconds since Ascending Node Crossing (ANX)
 - Column 7: Pass Duration (seconds)
 - Column 8 (optional, if Ground Site): Distance from site to Ground-Track [km]. It is regarded as positive distance when the site is located on the left hand side of the ground-track.
 - Column 8 (9): Ascending or Descending Pass (ASC/DESC)
 - Column 9 (10): Zone/Ground Site Name
 - Column 10 (11): Instrument Swath Name
- Last Row: End of file (EOF)

The CSV files can be opened with dedicated spreadsheet software (e.g. Excel, LibreOffice) or any text editor.

5.1.3.2 KML Files

The KML output file contains the same information as the CSV but presented graphically. The format of the provided KML files is defined in KML Version 2.3 standard (see [RD 02]).

The KML files can be opened with Google Earth v7 or higher.

5.1.3.3 HTML Files

The HTML output file contains the same information as the CSV but presented in a tabular format, ready to be displayed in a web browser. A CSS stylesheet (*overpass_table.css*) is provided as part of the package to apply a given style to the HTML elements. The HTML output file requires the CSS stylesheet to be located in the same folder.

The HTML files can be opened with any web browser (e.g. Firefox). Once opened in a web browser, it is possible to export the HTML report to PDF.

5.1.4 Example

5.1.4.1 Running the executable

The executable program can be called in the following way:

- From Mac OSX / Linux Terminal window

```
./ZoneOverPass input_config_file_S2A_MSI.txt 2016-06-06T00:00:00 2016-06-08T00:00:00
```

- From Windows command prompt window

```
ZoneOverPass.exe input_config_file_S2A_MSI.txt 2016-06-06T00:00:00 2016-06-08T00:00:00
```

The executable program shows the following messages:

```
Execution of program ZoneOverPass v2.0
```

```
Input data set by the user:
```

```
Satellite: SENTINEL2A
```

```
Orbit File:
```

```
./mission_configuration_files/SENTINEL2A/OSF/S2A_OPER_MPL_ORBSCT_20150625T073255_999999999T999999_0006.EOF
```

```
Swath File: ./mission_configuration_files/SENTINEL2A/SDF/SDF_MSI.S2
```

```
Swath ID: MSI
```

```
Zone File: EXAMPLE_ZONEDBFILE.EOF
```

```
Start Time: 2016-06-06T00:00:00
```

```
Stop Time: 2016-06-08T00:00:00
```

```
Start Time: 6001.000000000000
```

```
Stop Time: 6003.000000000000
```

```
Start Orbit: 4989
```

```
Stop Orbit: 5018
```

```
Output Filename KML:
```

```
S2A_EXAMPLE_CIRCLE_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.KML
```

```
Output Filename CSV:
```

```
S2A_EXAMPLE_CIRCLE_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.CSV
```

```
Output Filename HTML:
```

```
S2A_EXAMPLE_CIRCLE_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.HTML
```

```
Output Filename KML:
```

```
S2A_EXAMPLE_POINT_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.KML
```


```
Output Filename CSV:
```

```
S2A_EXAMPLE_POINT_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.CSV
```

```
Output Filename HTML:
```

```
S2A_EXAMPLE_POINT_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.HTML
```

```
Output Filename KML: S2A_AFRICA_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.KML
```



Output Filename CSV: S2A_AFRICA_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.CSV
 Output Filename HTML: S2A_AFRICA_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.HTML
 Output Filename KML: S2A_PACIFIC_AREA_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.KML
 Output Filename CSV: S2A_PACIFIC_AREA_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.CSV
 Output Filename HTML:
 S2A_PACIFIC_AREA_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.HTML
 Output files created successfully

5.1.4.2 Input File

Contents of the input configuration file used as example (input_config_file_S2A_MSI.txt):

```
SENTINEL2A
./mission_configuration_files/SENTINEL2A/OSF/S2A_OPER_MPL_ORBSCT_20150625T073255_99999999T999999_0006.EOF
EOF
./mission_configuration_files/SENTINEL2A/SDF/SDF_MSI.S2
EXAMPLE_ZONEDBFILE.EOF
MSI
500000ff
```

5.1.4.3 Output Files

5.1.4.3.1 CSV Files

Several CSV output files are created (on per zone in zone database file):

S2A_EXAMPLE_CIRCLE_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.CSV
 S2A_EXAMPLE_POINT_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.CSV
 S2A_AFRICA_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.CSV
 S2A_PACIFIC_AREA_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.CSV

Example ZONE output file

S2A_AFRICA_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.CSV:

	A	B	C	D	E	F	G	H	I	J	K	
1	FILENAME	S2A_AFRICA_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.CSV										
2	CREATION_DATE	2018-06-12T15:24:36										
3	EXECUTABLE_NAME_VERSION	ZoneOverPass_v2.0										
4	MISSION	SENTINEL2A										
5	ORBIT_FILE	./mission_configuration_files/SENTINEL2A/OSF/S2A_OPER_MPL_ORBSCT_20150625T073255_99999999T999999_0006.EOF										
6	ZONE	AFRICA										
7	VALIDITY_START	2016-06-06T00:00:00										
8	VALIDITY_STOP	2016-06-08T00:00:00										
9	PASS	UTC_TIME_START	ABS_ORB	ANX_TIME	UTC_TIME_STOP	ABS_ORB	ANX_TIME	DURATION[ASCENDIN	ZONE	SWATH	
10		1	2016-06-06T08:04:5	4994	2709.51278	2016-06-06T08:19:39	4994	3590.39923	880.886454	DESC	AFRICA	MSI
11		2	2016-06-06T09:42:0	4995	2494.59228	2016-06-06T09:51:21	4995	3050.44436	555.852081	DESC	AFRICA	MSI
12		3	2016-06-06T11:21:3	4996	2419.69083	2016-06-06T11:29:09	4996	2876.39784	456.707006	DESC	AFRICA	MSI
13		4	2016-06-06T19:06:4	5001	119.981559	2016-06-06T19:07:48	5001	185.651548	65.669989	ASC	AFRICA	MSI
14		5	2016-06-06T20:37:2	5001	5564.15809	2016-06-06T20:54:06	5002	521.888342	999.688426	ASC	AFRICA	MSI
15		6	2016-06-06T22:27:4	5003	96.122194	2016-06-06T22:35:48	5003	581.624151	485.501957	ASC	AFRICA	MSI
16		7	2016-06-07T07:36:5	5008	2836.6197	2016-06-07T07:40:21	5008	3045.03545	208.415743	DESC	AFRICA	MSI
17		8	2016-06-07T07:42:3	5008	3178.8175	2016-06-07T07:44:52	5008	3315.29066	136.473158	DESC	AFRICA	MSI
18		9	2016-06-07T09:11:4	5009	2484.27609	2016-06-07T09:26:31	5009	3372.79748	888.521392	DESC	AFRICA	MSI
19		10	2016-06-07T10:50:5	5010	2395.34603	2016-06-07T11:00:03	5010	2942.8409	547.494878	DESC	AFRICA	MSI
20		11	2016-06-07T20:10:1	5015	5742.04492	2016-06-07T20:24:09	5016	536.574156	836.48741	ASC	AFRICA	MSI
21		12	2016-06-07T21:47:2	5016	5530.87337	2016-06-07T21:51:43	5016	5791.33325	260.459878	ASC	AFRICA	MSI
22		13	2016-06-07T21:55:2	5016	6010.1818	2016-06-07T21:56:03	5017	8.881835	40.658204	ASC	AFRICA	MSI
23		14	2016-06-07T21:57:1	5017	76.513713	2016-06-07T22:05:57	5017	602.952671	526.438958	ASC	AFRICA	MSI
24	EOF											

Example of GROUND_SITE output file

S2A_EXAMPLE_CIRCLE_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.CSV:

	A	B	C	D	E	F	G	H	I	J	K	L
1	FILENAME	S2A_EXAMPLE_CIRCLE_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.CSV										
2	CREATION_DATE	2018-06-12T15:24:36										
3	EXECUTABLE_NAME_VERS	ZoneOverPass_v2.0										
4	MISSION	SENTINEL2A										
5	ORBIT_FILE	./mission_configuration_files/SENTINEL2A/OSF/S2A_OPER_MPL_ORBSCT_20150625T073255_99999999T999999_0006.EOF										
6	GROUND_SITE	EXAMPLE_CIRCLE										
7	GROUND_SITE_RADIUS[km]	5										
8	VALIDITY_START	2016-06-06T00:00:00										
9	VALIDITY_STOP	2016-06-08T00:00:00										
10	PASS	UTC_TIME_START	ABS_ORB	ANX_TIME	UTC_TIME_STOP	ABS_ORB	ANX_TIME	DURATION	DISTANC	ASCENDIN	GROUND_SITE	SWATH
11	1	2016-06-07T23:47:12	5018	636.203281	2016-06-07T23:47:14	5018	637.693558	1.490277	-37.481989	ASC	EXAMPLE_CIRCLE	MSI
12	EOF											

5.1.4.3.2 KML Files


Several KML output files are created (on per zone in zone database file):

S2A_EXAMPLE_CIRCLE_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.KML
 S2A_EXAMPLE_POINT_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.KML
 S2A_AFRICA_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.KML
 S2A_PACIFIC_AREA_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.KML


After loading the files with Google Earth, the overpass data can be found in the “Places” window, under “Temporary Places”.

Example of ZONE output file

S2A_AFRICA_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.KML:



When moving the mouse over the swaths, the lines are highlighted (increase in thickness and lighter in colour). Then by clicking on top of the track, a balloon showing additional information is displayed, namely the absolute and relative orbit number and the longitude and UTC time of the ascending node crossing of the selected orbit.



5.1.4.3.3 HTML Files

Several HTML output files are created (on per zone in zone database file):

S2A_EXAMPLE_CIRCLE_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.HTML
 S2A_EXAMPLE_POINT_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.HTML
 S2A_AFRICA_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.HTML
 S2A_PACIFIC_AREA_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.HTML

By double-clicking on the HTML file, it opens with the default browser, applying the style from CSS stylesheet.

Example of ZONE output file

[S2A_AFRICA_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.HTML](#):

ZONE OVERPASS TABLE HTML REPORT

Creation Date: 2018-06-12T12:13:59

Filename	S2A_AFRICA_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.HTML
Executable Name and Version	ZoneOverPass_v2.0
Mission	SENTINEL2A
Orbit File	./mission_configuration_files/SENTINEL2A/OSF/S2A_OPER_MPL_ORBSCT_20150625T073255_99999999T999999_0006.EOF
Zone	AFRICA
Validity Start	2016-06-06T00:00:00
Validity Stop	2016-06-08T00:00:00

Zone Overpass Table

Pass	UTC Time Start	Abs Orbit Start	ANX Time Start[s]	UTC Time Stop	Abs Orbit Stop	ANX Time Stop[s]	Duration[s]	Ascending / Descending	Zone	Swath
1	2016-06-06T08:04:58	4994	2709.512780	2016-06-06T08:19:39	4994	3590.399234	880.886454	DESC	AFRICA	MSI
2	2016-06-06T09:42:05	4995	2494.592276	2016-06-06T09:51:21	4995	3050.444357	555.852081	DESC	AFRICA	MSI
3	2016-06-06T11:21:32	4996	2419.690834	2016-06-06T11:29:09	4996	2876.397840	456.707006	DESC	AFRICA	MSI

Example of GROUND_SITE output file

[S2A_EXAMPLE_CIRCLE_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.HTML](#):

GROUND SITE OVERPASS TABLE HTML REPORT

Creation Date: 2018-06-12T12:13:59

Filename	S2A_EXAMPLE_CIRCLE_MSI_VISIBILITY_SEGMENTS_20160606_000000_20160608_000000_0001.HTML
Executable Name and Version	ZoneOverPass_v2.0
Mission	SENTINEL2A
Orbit File	./mission_configuration_files/SENTINEL2A/OSF/S2A_OPER_MPL_ORBSCT_20150625T073255_99999999T999999_0006.EOF
Ground Site	EXAMPLE_CIRCLE
Ground Site Radius	5.000000 km
Validity Start	2016-06-06T00:00:00
Validity Stop	2016-06-08T00:00:00

Ground Site Overpass Table

Pass	UTC Time Start	Abs Orbit Start	ANX Time Start[s]	UTC Time Stop	Abs Orbit Stop	ANX Time Stop[s]	Duration[s]	Distance to Ground-Track[km]	Ascending / Descending	Ground Site	Swath
1	2016-06-07T23:47:12	5018	636.203281	2016-06-07T23:47:14	5018	637.693558	1.490277	-37.481989	ASC	EXAMPLE_CIRCLE	MSI



Ref.: EOCFI-FTD-039
Issue: 2.1
Date: 27/07/2018
Page: 10 / 10

6. TECHNICAL DETAILS AND ASSUMPTIONS

6.1 Earth Observation CFI Software Version

The executable has been created using EO CFI SW libraries v4.14.